

# BATTERY PACK (12 Cell Part #18510)



## BATTERY PACK SIZE

<b>Diameter</b>	2.6" Max (6.6cm)
<b>Length</b>	10.25"(26 cm)
<b>Weight</b>	~2.4 lb (~1.1 kg)

## WEIGHT 2.8lb/ 1.3k g

<b>Operating Voltage range</b>	2.5VDC to 4.2VDC / 3.6v Rated
<b>Nominal Capacity</b>	192,000 mAh/100 days @ 80mA 10°C
<b>Maximum Discharge Current</b>	230 mAmps DC
<b>Connectors</b>	4 Pos Connector
SR3001 connector	

## LI Content (5g each cell) Approx 60g total

Individual battery cells	U.L. Component Recognition, MH 12193
UN. 38.3 Transport Tested	

## TEMPERATURE RATINGS

<b>Operating (Discharge)</b>	-55°C to +85°C
------------------------------	----------------



**ATS**  
ADVANCED TELEMETRY SYSTEMS

**VISIT [WWW.ATSTRACK.COM](http://WWW.ATSTRACK.COM)**

470 First Ave NW, Isanti, MN 55040  
763-444-9267 | 763-444-9384 fax  
email: [sales@atstrack.com](mailto:sales@atstrack.com) | [www.atstrack.com](http://www.atstrack.com)